

HX-5B-WP

SPEAKER SYSTEM

The HX-5B-WP is a 2-way compact speaker system that permits both constant directivity control over a wide frequency range and changes in directivity. It is ideal for reproducing clear sound in spaces with long reverberation times or high background noises. The HX-5B-WP is designed for outdoor use.



Order no: HX-5B-WP EU

Specifications

Frequency response	95 Hz - 20 kHz (60° mode)
Connection	2-core cabtyre cord with diameter of 6 mm
Sensitivity (1#V, 1#m) (combined)	96 dB (60° mode), 97 dB (45° mode), 98 dB (30° mode), 99 dB (15° mode)
Speaker component	Low frequency: 12 cm cone-type x 4, High frequency: Balanced dome-type x 12
Directivity angle horizontal	100 °
Directivity angle vertical	60 °
Rated impedance	8 Ω
Crossover frequency	4 kHz
Power handling capacity	Continuous pink noise: 200 W / Continuous program: 600 W
Weight	16,0 kg
Certificates	IPX4, Ball-proof
Dimensions (W x H x D)	408 x 546 x 342 mm
Dimensions (ø x D)	x 342 mm
Gross weight	21,2 kg
Finish	Polypropylene resin, paint, black (RAL 9005 or equivalent)

HX-5B-WP

SPEAKER SYSTEM

Appearance

