

N-8000DI

DIRECT SELECT UNIT

The N-8000DI is a Direct select unit designed for use with TOA's packet intercom system (IP network-compatible intercom system) that employs the packet audio technology. It is equipped with each 32 contact inputs and outputs, and the indicators on the front panel indicate the output statuses. Connecting the unit to the LAN permits the calling station display, external equipment control, and direct selection function to be realized. It can be mounted in an EIA equipment rack (1U size) with the use of an accessory rack mounting bracket or installed on a wall using an optional wall mounting bracket.



Order no: N-8000DI CE-GB
Alternative products: N-8000AL, N-8000CO,
N-8000DI, N-8000MI

Specifications

Network	10BASE-T/100BASE-TX (Automatic-Negotiation)
Network protocol	TCP/IP, UDP, ARP, ICMP, HTTP, RTP, IGMP
Power source	220 - 240 V AC, 50 / 60 Hz
Audio packet transmission system	Unicast, Multicast
Power consumption	16 W (max.)
Inputs	Contact: 32 inputs, no-voltage make contact input, open voltage: 24 V DC, short-circuit current: 5 mA or less, removable terminal block (20 pins)
Outputs	Contact: 32 outputs, relay contact output, contact capacity: 24 V DC / 2 - 500 mA, removable terminal block (32 pins)
Power source	220 - 240 V AC, 50 / 60 Hz
Inputs	Contact: 32 inputs, no-voltage make contact input, open voltage: 24 V DC, short-circuit current: 5 mA or less, removable terminal block (20 pins)
Outputs	Contact: 32 outputs, relay contact output, contact capacity: 24 V DC / 2 - 500 mA, removable terminal block (32 pins)
Weight	2,8 kg
Dimensions (W x H x D)	420 x 44,3 x 267 mm
Dimensions (ø x D)	x 267 mm
Gross weight	4,2 kg
Finish	Steel plate, pre-coated, 30% gloss, black
Operating humidity	90 % RH or less (no condensation)
Operating temperature	0 °C to +40 °C



N-8000 Series

N-8000DI

DIRECT SELECT UNIT

Appearance