

# N-8031MS

MASTER STATION

The N-8031MS is a flush- or surface-mount master station designed to operate in conjunction with TOA IP Intercom Exchange and features high quality hands-free conversation. Connecting a foot switch or other external switch to the external dial input terminal permits one-touch dialing operation by way of such switches. Handset conversation can be established in conjunction with the optional RS-191.



Order no: N-8031MS Y  
 Alternative products: N-8600MS, N-8610RM,  
 N-SP80MS1

## Specifications

Power source	48 V DC (supplied from the IP network intercom exchange)
Frequency response	300 Hz - 7 kHz
Power consumption	2.4 W (max.)
Outputs	No-voltage make contact input, open voltage: 5 V DC, short-circuit current: 1 mA, screwless connector (5 pins)
Wiring method	1 set of twisted pair cable
Transmission range	Max. 1500 m (ø 0.65 mm, Loop resistance < 170 Ω) / 2,900 m (ø 0.9 mm)
Speech method	Hands-free or handset conversation
Weight	0,8 kg
Dimensions (W x H x D)	115 x 254 x 54,6 mm
Dimensions (ø x D)	x 54,6 mm
Gross weight	1,3 kg
Finish	Stainless steel, hairline,

# N-8031MS

MASTER STATION

Appearance

