

NX-300W

NETWORK AUDIO ADAPTER

The TOA NX-300 is a network audio adapter that utilizes packet audio technology which makes it possible to transmit high-quality audio signals in real time. Connecting the NX-300 to a network (LAN or WAN) permits high-quality audio or contact control signals to be transmitted in real time. As existing networks can be used, systems can be constructed with no need for the installation of new wiring. Broadcasts using audio files and up to 8 different levels of priority control can also be made, and provided by stations, factories or other central facilities to individual bases. It can be mounted in an EIA equipment rack (1U size) with the use of an optional rack mounting bracket or installed on a wall using an optional wall mounting bracket.



Order no: NX-300 W


Specifications

Power source	24 V DC
Current consumption	310,0 mA
Control input	8 (12 V DC, 10 mA)
Control output	8 (open collector, 30 V DC, 50 mA), 2 Relais
Network	RJ45, 10BASE-T/100BASE-TX, automatic
Audio input	Balanced, sensitivity -58/0 dBV selectable
Audio output	Balanced, 0 dBV, min. 600 Ω
Weight	1,2 kg
Dimensions (W x H x D)	210 x 44 x 188 mm
Dimensions (ø x D)	x 188 mm
Gross weight	2,18 kg
Finish	Steel plate, paint, black
Operating humidity	90 % RH or less (no condensation)
Operating temperature	-10 °C to +50 °C (0 °C to +40 °C when AC adapter is in use)


NX-300W

NETWORK AUDIO ADAPTER


Appearance



Rear View



Front View



Side View

UNIT:mm

SCALE:1/2