

# PC-245AB-EB

Ceiling Speaker with Fire Dome

A/B wiring  
 Fire dome prevents passing the flames into the ceiling  
 2 separate 100 V transformer and 2 x 6 W speaker  
 Easy installation  
 Certified according to EN 54-24  
 Compliant with BS-5839-8



Order no: PC-245AB-EB  
 Alternative products: VM-3360VA,  
 VM-3240VA, VP-2421, VP-2421incl, VP-2241,  
 VP-2241incl, VP-2122incl, VP-2122, VP-2064,  
 VP-2064incl, VP-3504, VP-3154, VP-3304,  
 SX-2000SM, VX-2000, VX-3008F, VX-3004F,  
 VX-3016F

## Specifications

Frequency response	150 Hz - 20 kHz (-10 dB from sensitivity)
Connection	2 ceramic screw terminals, thermal fuse
Sensitivity (1#V, 1#n) (combined)	91 dB (both speaker chassis driven)
Speaker component	2 x 5"x3" full range dual cone (A/B 2-lines)
Rated input	6 W
Tappings	6 / 3 / 1.5 W (100 V)
Mounting hole	220,00 mm
Weight	2,0 kg
Certificates	EN 54-24, BS, IP32, Ease
Dimensions (W x H x D)	x 131
Dimensions (ø x D)	245 x 131 mm
Gross weight	2,1 kg
Finish	traffic white (RAL 9016 or equivalent)



EN 54 certified speakers

# PC-245AB-EB

Ceiling Speaker with Fire Dome

---

Appearance