

PC-275AB-EB

Surface Ceiling Mount Speaker

A/B wiring Only 86 mm depth 2 separate 100 V transformer and 2 x 6 W speaker Quick-mount Certified according to EN 54-24 Compliant with BS-5839-8



Order no: PC-275AB-EB
 Alternative products: VM-3360VA,
 VM-3240VA, VP-2421, VP-2421incl, VP-2241,
 VP-2241incl, VP-2122incl, VP-2122, VP-2064,
 VP-2064incl, VP-3504, VP-3154, VP-3304,
 SX-2000SM, VX-2000, VX-3008F, VX-3004F,
 VX-3016F

Specifications

Frequency response	180 Hz - 20 kHz (-10 dB from sensitivity)
Connection	2 ceramic screw terminals, thermal fuse
Sensitivity (1#V, 1#m) (combined)	91 dB (both speaker chassis driven)
Speaker component	2 x 5"x3" full range, dual cone (A/B 2-lines)
Rated input	6 W
Tappings	6 / 3 / 1.5 W (100 V)
Weight	1,5 kg
Certificates	EN 54-24, BS, IP32, Ease
Dimensions (W x H x D)	x 86,5
Dimensions (ø x D)	274,4 x 86,5 mm
Gross weight	2,04 kg
Finish	white



EN 54 certified speakers

PC-275AB-EB

Surface Ceiling Mount Speaker

Appearance