

The PE-154EN is an EN 54 certified pendant loudspeaker for use in voice alarm systems. The two-way loudspeaker is suitable for announcement and music applications and convinces with a wide frequency range and stylish design. A directly attached, sturdy suspension cable can be extended up to 5 meters.



Order no: PE-154EN  
 Alternative products: VX-3008F, VX-3004F,  
 VX-3016F, SX-2000SM, VX-2000,  
 VM-3360VA, VM-3240VA, VM-3240E,  
 VM-3360E, VP-3504, VP-3154, VP-3304,  
 VP-2421incl, VP-2421, VP-2241, VP-2241incl,  
 VP-2122incl, VP-2122, VP-2064, VP-2064incl

## Specifications

Frequency response	70 Hz - 20 kHz
Connection	Ceramic screw terminals, thermal fuse
Sensitivity (1#V, 1#m) (combined)	91 dB (500 Hz – 5 kHz, pink noise)
Speaker component	Low: 5" cone-type, High: 1" balanced dome tweeter
Rated input	15 W
Tappings	15 / 10 / 5 W (100 V), 7.5 / 5 / 2.5 W (70 V)
Rated impedance	100 V
Dimensions (W x H x D)	186 x 251 mm
Finish	HIPS resin, off-white (RAL 9010 or equivalent)

Appearance

