

# RM-200SF

## SX-2000 FIREMAN'S MICROPHONE

The RM-200SF is a Fireman's Microphone of the matrix system. It is equipped with an Emergency key, permitting it to be used as a remote microphone for emergency broadcast. Zone selection and microphone announcement can be made at the time of emergency broadcast. It offers a surveillance function to detect failures including microphone element failure. The RM-200SF has three function keys that can be set as individual or group selection keys, and each key is linked with the corresponding two indicators. Connecting the optional RM-210, RM-320F Extension units to the RM-200SF expands the number of function keys and indicators in blocks of ten.



Order no: RM-200SF  
 Alternative products: RM-320F, RM-200SA,  
 VX-3004F, VX-3008F, VX-3016F, SX-2000SM


### Specifications

Power source	24 V DC (operating range: 15 – 40 V DC)
Frequency response	200 Hz - 15 kHz
Distortion	< 1 %
S/N ratio	55 dB
Audio output	0 dBV, 600 Ω, balanced
Controls	Volume control: Microphone, speaker
Key extension	5
Type	Dynamic microphone AGC
Directivity	Unidirectional
Dimensions (W x H x D)	200 x 215 x 95 mm
Dimensions (ø x D)	x 95 mm
Finish	ABS resin, bluish grey (PANTONE 538 or equivalent)


# RM-200SF

## SX-2000 FIREMAN'S MICROPHONE


Appearance



Front View



Side view with wall mounting bracket unit



Rear View